

C15 ACERT

500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Emissions: U.S. EPA Certified for Stationary Emergency Use Only (Tier 2 Nonroad Equivalent Emission Standards)



C15 ACERT
500 ekW/ 625 kVA
60 Hz/ 1800 rpm/ 480 V

Image shown may not reflect actual configuration

Metric English

Package Performance		
Genset Power Rating with Fan @ 0.8 Power Factor	500 ekW	
Genset Power Rating	625 kVA	
Aftercooler (Separate Circuit)	N/A	N/A

Fuel Consumption		
100% Load with Fan	137.0 L/hr	36.2 gal/hr
75% Load with Fan	110.5 L/hr	29.2 gal/hr
50% Load with Fan	71.3 L/hr	18.8 gal/hr
25% Load with Fan	41.9 L/hr	11.1 gal/hr

Cooling System ¹		
Engine Coolant Capacity	20.8 L	5.5 gal

Inlet Air		
Combustion Air Inlet Flow Rate	38.2 m ³ /min	1347.7 cfm
Max. Allowable Combustion Air Inlet Temp	49 ° C	120 ° F

Exhaust System		
Exhaust Stack Gas Temperature	531.1 ° C	988.0 ° F
Exhaust Gas Flow Rate	102.1 m ³ /min	3605.5 cfm
Exhaust System Backpressure (Maximum Allowable)	10.0 kPa	40.0 in. water



C15 ACERT

500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Emissions: U.S. EPA Certified for Stationary Emergency Use Only (Tier 2 Nonroad Equivalent Emission Standards)

Heat Rejection		
Heat Rejection to Jacket Water	182 kW	10375 Btu/min
Heat Rejection to Exhaust (Total)	493 kW	28039 Btu/min
Heat Rejection to Aftercooler	121 kW	6860 Btu/min
Heat Rejection to Atmosphere from Engine	91 kW	5182 Btu/min
Heat Rejection to Atmosphere from Generator	29 kW	1655 Btu/min

Alternator²	
Motor Starting Capability @ 30% Voltage Dip	1428 skVA
Current	752 amps
Frame Size	LC6114F
Excitation	SE
Temperature Rise	130 ° C

Emissions (Nominal)³		
NOx	2129.1 mg/Nm ³	4.6 g/hp-hr
CO	301.5 mg/Nm ³	0.6 g/hp-hr
HC	8.8 mg/Nm ³	0.0 g/hp-hr
PM	9.5 mg/Nm ³	0.0 g/hp-hr

DEFINITIONS AND CONDITIONS

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

C15 ACERT

500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

**Emissions: U.S. EPA Certified for Stationary Emergency
Use Only (Tier 2 Nonroad Equivalent Emission Standards)**

Applicable Codes and Standards:

AS1359, CSA C22.2 No100-04, UL142,UL489, UL869, UL2200,
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,
NEMA MG1-22,NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

STANDBY:Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

Fuel Rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

www.Cat-ElectricPower.com

Performance No.: DM8155-04

Feature Code: C15DECF

Generator Arrangement: 4183867

Date: 12/01/2016

Source Country: U.S.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.